


# MPX130 Triple-deck PCB Terminal Strip



## DIMENSIONS/POSITIONS

	MPX130-500	MPX130-508
Pitch	5.00mm	5.08mm
Poles	6 ~ 72Poles	6 ~ 72Poles
Dimension A	5.00mm	5.08mm
Length	A= 5.00xP/3+1.00mm(P≥6)	A= 5.08xP/3+1.00mm(P≥6)
Housing Material	PA 66	PA 66
Cover	PA 66	PA 66
Contact	Copper, Tin Plated	Copper, Tin Plated
Spring	Stainless Strip Steel	Stainless Strip Steel
Wire Size	12 ~ 28AWG	12 ~ 28AWG
PCB Hole Diameter	1.3mm	1.3mm
Operating Temperature	-40°C to +105°C	-40°C to +105°C

## TECHNICAL DATA

Connection in acc. with standard EN-VDE		
Nominal Current I <sub>N</sub>	10A	10A
Nominal Cross Section	2.5mm <sup>2</sup>	2.5mm <sup>2</sup>
Maximum load current	10A	10A
Insulating Material	PA	PA
Inflammability class acc. to UL94	V0	V0
Nominal voltage, UL/CUL	300V	300V
Nominal current, UL/CUL	10A	10A

