



MH4B Series

40mm Panel Mount Dome-type Illuminated Buzzer



- Robust, efficient, and easy-to-install
- Mounting hole diameter: $\varnothing 20\text{-}22\text{ mm}$
- Red LED is on or blinks when the buzzer operates
- Buzzer volume: $80\pm 5\text{ dB}$
- IP65 protection (front side)

Ordering Information

MH4B - C 02 F - Y
 ① ② ③ ④

① Product type	C	Cable wiring type
	P	M12 connector plug type
② Voltage	01	12VDC
	02	24VDC
③ Sound type	F	Intermittent sound
	D	Continuous sound
④ Front cover color	Y	Yellow
	B	Black
	W	Dark Ivory

Specifications



Buzzer volume	$80\pm 5\text{ dB}$ (at 1 m distance)	
Sound type	Intermittent sound , Continuous sound	
Fixing hole	$\varnothing 20 \sim \varnothing 22\text{ mm}$	
Indicator light	Red LED (intermittent sound - LED flashing, continuous sound - LED on)	
Material	ABS resin(body and fixing nut) , PC resin(cover), M12 Connector Plug - Steel	
Insulation Resistance	$\geq 1,000\text{ M}\Omega$ (500VDC Mega standard)	
Withstand voltage	500VAC, 50/60Hz for 1 minute (between power terminal and case)	
Vibration-resistant	30Hz (1 minute cycle) 1 hours double amplitude 0.5mm in X, Y, Z respective direction	
Ambient temperature	$-15 \sim 50^\circ\text{C} / 5^\circ\text{F} \sim 122^\circ\text{F}$ (no freezing)	
Storage temperature	$-25 \sim 65^\circ\text{C} / -13^\circ\text{F} \sim 149^\circ\text{F}$ (no freezing)	
Ambient humidity	35~85% RH (no condensation)	
Degree of protection	IP65 (front side)	
Certification	RoHS	

Power supply	12VDC $\pm 10\%$	24VDC $\pm 10\%$
Power supply	1color type: 40g	1color type: 116g
Current consumption	intermittent $\geq 30\text{ mA}$ continuous $\geq 40\text{ mA}$	intermittent $\geq 30\text{ mA}$ continuous $\geq 40\text{ mA}$

Cable spec.	MH4B-C type	UL2464, 22AWG, material: PVC, External dimensions: $\varnothing 4\text{ mm}$, 700mm Allowable cable bending radius: 30 mm
Weight	MH4B-C	$\approx 44\text{ g}$
	MH4B-P	$\approx 50\text{ g}$

External Dimensions


unit: mm




MH4B-P type M12 Connector Assembly Dimension

unit: mm



< Straight connector type >



< L type connector type >



When installing the panel




M12 connector wiring specifications (sold separately)

unit: mm

M12 cable (4-wire, Socket-Female)	Connection straight type		Connection part L-shaped	
	Product Name	Length	Product Name	Length
	CIDH4-2	2m	CLDH4-2	2m
CIDH4-3	3m	CLDH4-3	3m	
CIDH4-5	5m	CLDH4-5	5m	

< Socket - Female, Straight >



< Socket - Female, L type >

